


Stub End Turnbuckles

HS-251




- End fittings are Quenched and Tempered or Normalized, bodies heat treated by normalizing.
- Complete assembly is self-colored.
- Reference American Welding Society Specifications for proper welding procedures.
- Meets the performance requirements of Federal Specifications FF-T-791b, Type 1 Form 1 - CLASS 3, and ASTM F-1145, except for those provisions required of the contractor.

HS-251 Stub End Turnbuckles



Shank Diameter & Take up (in.)	Shank Diameter & Take up (mm)	HS-251 Stock No.	Working Load Limit (t)	Weight Each (kg)	Dimensions (mm)					
					A	R	S	T	U	W
3/8 x 6	9.53 x 152	1033143	.54	.34	9.65	152	181	14.2	113	406
1/2 x 6	12.7 x 152	1033161	1.00	.57	12.7	152	190	19.1	108	406
5/8 x 6	15.9 x 152	1033223	1.59	.96	16.0	305	200	23.8	103	406
3/4 x 6	19.1 x 152	1033287	2.36	1.48	19.1	152	209	28.7	111	431
7/8 x 6	22.2 x 152	1033367	3.27	2.17	22.4	152	219	33.2	119	457
1 x 6	25.4 x 152	1033429	4.54	2.88	25.4	152	228	38.1	127	482
1 x 12	25.4 x 305	1033447	4.54	3.99	25.4	304	381	38.1	127	635
1-1/8 x 6	28.6 x 152	1033508	5.62	4.03	28.7	152	231	39.6	125	482
1-1/4 x 6	31.8 x 152	1033526	6.89	4.62	31.8	152	231	39.6	138	508
1-1/4 x 12	31.8 x 305	1033544	6.89	6.17	31.8	304	384	39.6	138	660
1-1/2 x 12	38.1 x 305	1033642	9.71	9.27	38.1	304	400	47.7	137	673

LOCK NUTS



HG-4060 / HG-4061 Lock Nuts

Thread Diameter (in.)	Right Hand HG-4060 Stock No.	Left Hand HG-4061 Stock No.	Weight Per 100 (kg)	Dimensions (mm)		
				O	P	Q
1/4	1075115	1075491	.36	11.2	12.7	4.05
5/16	1075133	1075516	.59	12.7	14.2	4.85
3/8	1075151	1075534	.91	14.2	16.3	5.60
1/2	1075197	1075570	1.81	19.1	21.8	7.85
5/8	1075213	1075598	3.18	23.9	26.9	9.65
3/4	1075231	1075614	4.99	28.7	32.0	10.7
7/8	1075259	1075632	7.39	33.3	38.1	12.2
1	1075277	1075650	10.8	38.1	42.9	14.0
1-1/8	1075295	1075678	14.5	38.1	42.9	14.0
1-1/4	1075311	1075696	28.3	47.8	54.0	18.3
1-1/2	1075357	1075730	32.7	57.0	64.5	21.3
1-3/4	1075393	1075776	51	70.0	81.0	25.4
2	1075419	1075794	68	79.0	91.5	28.4
2-1/2	1075455	1075838	150	98.5	114	38.1
2-3/4	1075473	1075856	193	108	125	41.1