

Grade 80 Alloy Chain

SPECTRUM 80[®] ALLOY CHAIN



- Alloy Steel.
- Heat Treated.
- Finish - Black rust preventative coating.
- Permanently embossed with manufacturer's marking and 8(Grade).
- Proof Tested to 2.5 times the Working Load Limit with certification.
- Standard container - fiber drum

GRADE 80 ALLOY CHAIN recommended for overhead lifting applications.

Chain Size (mm)	Spec.8 Stock No.	Meters Per Drum	Dimensions (mm)	Working Load Limit (t)*	Weight Per Meter (kg)
6	1244915	200	6 x 18	1.12	.80
7	1244985	200	7 x 21	1.50	1.05
8	1245055	200	8 x 24	2.00	1.25
10	1245125	200	10 x 30	3.15	2.20
13	1245195	100	13 x 39	5.30	3.80
16	1245265	100	16 x 48	8.00	5.70
19	1245356	50	19 x 54	11.2	8.03
22	1245426	50	22 x 66	15.0	10.9
26	1245496	-	26 x 78	21.2	15.2
32	1245566	-	32 x 96	31.5	23.0

* Proof Loaded at 2.5 times the Working Load Limit. Minimum Ultimate Load is 4 times the Working Load Limit.

Crosby provides two methods of attaching Spectrum 8[®] chain to Crosby fittings



**A-1337
Lok-A-Loy[®]
Connecting Link
Refer to Page 202**



**S-1325
Grade 100
Coupler link
Refer to page 211**