

## CYCLONE locking pulley, alloy

**P201**

### Heavy-duty hauling pulley with locking cam

**Features:**

- 50mm, low friction integrated pulley wheel
- Unique 'X Cam™' locking mechanism
- Lightweight alloy construction
- 100kg Working load

Specifically designed for technicians to aid hauling of equipment and materials.

X-cam has a more advanced tooth design than traditional cams and is more suitable for industrial applications as it does not pluck the rope, so reducing rate of rope wear.

- Does not jam, even against knots
- Provides high degree of grip on ropes of varying condition including after rupture of the sheath

NB: Not certified for lifting persons.

The Cyclone is available as part of the Basic lifting kit. The kit includes all the components required to lift small loads.

**Specifications:**

*NB: specifications and colour may change without notice.*

Size: 10.5mm - 11mm rope

EN Test Mass: n/a

Loading: 100kg WLL for rope locking cam (F.O.S. 5:1), 300kg WLL for Pulley ONLY ( F.O.S. 5:1)

Conformity: UKCA & CE EN 13157:2004 +1A:2009

Materials: Anodised Aluminium Alloy, Stainless Steel Cam, Nylon

Weight (kg): 0.37

Industries: Renewables, construction, telecoms

**All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable**

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: [admin@heightec.com](mailto:admin@heightec.com)

[heightec.com](http://heightec.com)

PDS285

10/02/22