




# VPH-RS GO



## **VACUUM-POWER-HANDY VPH**

Flexible and powerful hand operated laying device for dense products, such as granite or high quality concrete elements up to 150 kg weight.

### **Consisting of the following components:**

Vacuum pump unit with manometer and suction force indicator, battery charging indicator and on/off switch. Complete unit detachable, can also be mounted on other devices.

### **Special features:**

Special seal, consisting of 2 components for optimised sealing. Even when the suction plate is sitting on sharp edges for a long time, no permanent marks are left in the seal. Therefore no "foldable rests" are necessary to save guard the seal.

▶ Highly wear-resistant seal!

Powered by rechargeable battery 12 V. Special energy saving automatic allows a full day of laying operation without the need of recharging.

Handle for 2 men operation, handles height and width adjustable to accomodate with different laying tasks.

- **►** With Suction plate
- Galvanised
- The seal can be exchanged without glue and any tool within 1 minute.
- Additionally equipped with lifting eyelet for crane hook (only allowed to work near the ground!).

Туре	Carrying Capacity kg (lbs)	Dead Weight kg (Ibs)	Suction Plate Dimension mm (in)	Order-Number
VPH-100 <sup>©</sup>	100 (220)*	16 (35)	oval 260 x 210 (101/4" x 81/4")	5271.0002
VPH-150 <sup>©</sup>	150 (330)*	16,5 (36)	oval 440 x 250 (171/4" x 93/4")	5271.0001
VPH-SPS-HP-	4270.0051			
VPH-SPS-HP-	4270.0050			
Battery-12V	ttery-12V/6,5 Ah Spare storage battery for VPH-100 and 150			2420.0007
VPH-LG-220	<b>V/12V</b> Bat	/12V Battery charger for VPH-100 and 150		
VPH-ED-SPS-	HP-100 Rep	olacement sec	4273.0004	
VPH-ED-SPS-HP-150 Replacement seal for VPH-SPS-HP-150-44/25			4273.0012	

Value at 500 mbar low pressure

# Accessory

# Wheel Set VPH-RS

Retrofit with wheel set VPH-RS can be done at any time.

Thus dense slabs can be installed by just one person.

# **Chain Box KF**

The chain box with integrated safety chain is available as an optional extra.

For proper safety at work the chain has to be attached underneath the load.

Туре		Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
VPH-RS ●		150	7,6	4271.0072
KF	Chain box with chain for MJ-II, VPH und MJ-J-II		3	4271.0098

• Durable surface protection by galvanizing