

# Crosby® Grade 100 Clevis Hooks

**Fatigue Rated**

**"QT"**  
QUENCHED & TEMPERED


QUIC-CHECK®

**Crosby 8/10™**

A-1339



- Forged Alloy Steel - Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- Hoist hooks incorporate two types of strategically placed markings forged into the product which address two (2) QUIC-CHECK® features: Deformation Indicators and Angle Indicators.
- Low profile hook tip.
- New integrated latch (S-4320/S-4339) meets the world standard for lifting.
  - Heavy duty stamped latch interlocks with the hook tip.
  - High cycle, long life spring.
  - When secured with the proper cotter pin through the hole in the tip of hook, meets the intent of OSHA Rule 1926.550(g) for personnel lifting.
- Suitable for use with Grade 100 chain in overhead lifting applications as long as hook is Proof Tested as part of the chain sling assembly or as an individual component. Per ANSI B30.9-1.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."
- Meets the performance requirements of EN1677-2:2007 when assembled with a latch.



## A-1339 Clevis Sling Hook

Chain Size		Working Load Limit (t)*	Hook ID Code	A-1339 Stock No.	L-1339 Stock No.	Weight Each (kg)	Dimensions (mm)								S-4320 Rep. Latch Stock No.	S-4339 Rep. Latch Stock No.
(in.)	(mm)						D	G	J	L	M	R	AA			
-	6	1.5	DA	1048982	1049103	0.29	72.6	18.5	23.6	107	16.0	74.9	38.1	1096325	-	
1/4	7	2.0	HA	1048991	1049112	0.72	98.0	26.4	30.2	144	19.1	101	50.8	1096468	-	
5/16	8	2.6	HA	1049000	1049121	0.71	98.0	26.4	30.2	144	19.1	100	50.8	1096468	-	
3/8	10	4.0	IA	1049009	1049130	1.17	111	30.2	38.9	171	25.4	120	63.5	1096515	-	
1/2	13	6.8	JA	1049018	1049149	2.39	142	36.6	45.2	213	29.7	150	76.2	1096562	-	
5/8	16	10.3	KA	1049027	1049158	4.45	172	48.0	61.2	259	36.6	177	102	1096609	-	
3/4	18-20	16.0	-	1049036	1049167	8.30	211	71.9	68.3	332	50.0	203	114	-	1048714	
7/8**	22-23**	20.0	-	1049045	1049176	11.2	233	78.0	77.5	355	50.0	223	127	-	1048732	

\* Ultimate Load is 4 times the Working Load Limit.

\*\* 7/8 in. (22-23 mm) size does not have cam, latch attaches to unique pin.